

AN/PRC-117G(V)1(C)
TYPE-1 WIDEBAND MULTIBAND
MULTIMISSION RADIO
WITH INTERNAL SAASM GPS



NSA CERTIFIED

A revolutionary CNR-sized radio
with US/NATO standardized
waveforms and wideband
data capabilities

The Falcon III® AN/PRC-117G(V)1(C) manpack is a software defined tactical radio that provides breakthrough wideband data performance and interoperability with fielded waveforms. This single channel radio covers 30 MHz to 2 GHz and is 30% smaller and 35% lighter than currently fielded multiband manpack radios. The radio operates off a single standard battery, further reducing the weight of a dismounted radio yet maintaining peak transmit power of 10 watts VHF and 20 watts UHF.

The AN/PRC-117G features a JTEL-certified Software Communications Architecture (SCA) operating environment, providing the optimal transition to software-defined radio technology. The AN/PRC-117G provides SINCGARS, Havequick II, VHF/UHF AM and FM, DAMA, 181B Dedicated Channel TACSAT, High Performance Waveform (HPW), and the Harris Adaptive Networking Wideband Waveform (ANW2). The ROVER L-Band receive waveform is also available as an option. Future planned software upgrades include IW, MUOS, SATURN, and SRW waveforms (subject to NSA approval).

AN/PRC-117G networking capabilities can be enhanced using the RF-7800B series of Broadband Area Global Network (BGAN) terminals. The RF-7800B BGAN terminals provide satellite-based wideband beyond-line-of-sight (BLOS) communications. When combined with the AN/PRC-117G, the system provides automatic and secure range extension, connection to out-of-range networks, and entry into the Internet or remote private networks.

Secured by the Harris Sierra™ II software programmable encryption module, the AN/PRC-117G is certified to carry up to US Top Secret voice and data traffic. The Sierra II, designed to maximize battery life in battery-powered radios, supports all JTRS COMSEC and TRANSEC requirements. The radio supports HAIFE® in-line encryption for secure network connectivity. Numerous legacy encryption modes are also supported, including KY-57/MINSON, ANDVT/KYV-5, KG-84C, and keyfill modes of DS-101 and DS-102.

The AN/PRC-117G stores multiple mission fill files, extending the time between reconfigurations. It also includes an embedded SAASM GPS receiver to display local position and provide automatic position reporting for situational awareness on the battlefield. Three separate antenna connections allow efficient and flexible use of antennas. The AN/PRC-117G(V)1(C) includes the R/T, manuals, H-250 handset, radio programming application, and programming cable.



Specifications for the AN/PRC-117G(V)1(C)

General	
RT Nomenclature	RT-1949(P)(C)
Frequency Range	30 MHz-2 GHz Narrowband (NB): VHF Low: 30-90 MHz VHF High: 90-225 MHz UHF Low: 225-512 MHz SATCOM UHF Low: 243-270 MHz and 292-318 MHz Wideband (WB): UHF: 225 MHz-2 GHz
Channel Spacing	NB: 5 kHz, 6.25 kHz, 8.33 kHz, 12.5 kHz, 25 kHz SATCOM: 5 kHz, 25 kHz WB: 500 kHz, 1.2 MHz, 2.5 MHz, 5 MHz
Net Presets	100
Data Interfaces	Ethernet, RS-232/RS-422, USB Synchronous and Asynchronous
Control Interfaces	Ethernet, RS-232, RS-422, USB
Management Tool	Windows-based Radio Programming Application
Software Environment	JTEL Certified SCA 2.2
Integrated GPS	SAASM
Frequency Stability	0.5 ppm
Frequency Tuning	10 Hz from 30 MHz-512 MHz 100 Hz from 513 MHz-2 GHz
Remote Control	RS-232 ASCII based

Modes and Waveforms	
Narrowband Waveforms	AM/FM, VHF/UHF LOS SINCGARS Havequick I and II
Wideband Waveforms	ANW2 ROVER III L-Band Receive (optional)
UHF SATCOM Waveforms	MIL-STD-188-181B Dedicated Channel MIL-STD-188-182A, 183A DAMA HPW
Voice and Data Modes	Simplex or Half-duplex MIL-STD-188-113 CVSD STANAG 4198 LPC-10e STANAG 4591 MELPe
Data Modes	Synchronous Data (300, 600, 1200, 2400, 12k, 16k bps) SINCGARS ECCM (VHF Low band/1200, 2400, 4800, 9600) Wideband FSK Cipher Text Digital Data (16 Kbps; KY-57) Narrowband Cipher Text Digital Data (2.4 Kbps; ANDVT/KYV-5) KG-84C Havequick III ECCM (16 Kbps; KY-57 UHF band only)

Security	
Encryption	Sierra™ II Based Type-1
Encryption Modes	KY-57, KYV-5, KG-84, HAIPE®, AES
Key Fill Device Compatibility	AN/CYZ-10 DTD, KOI-18, KYK-13, KYX-15, MX-18290, AN/PYQ-10, KIK-20
Key Storage	Up to 300
Mission Fill Device Compatibility	Windows-based Communications Planning Application

Power	
Power Input	19-34 VDC
Power Consumption	65 W max
Battery Types	BA-5590/U, BA-5390/U, BB-590/U, BB-390/U, BB-2590/U

Physical and Environmental	
Size (no handles)	7.4 W x 3.7 H x 8.8 D in. (without battery) 7.4 W x 3.7 H x 13.5 D in. (with battery)
Weight	8 lbs. (without battery) 12 lbs. (with battery)
Shock/Vibration	MIL-STD-810F for tracked vehicles, wheeled vehicles, shipboard
Immersion	1 meter
Color	CARC Green 383

Transmitter	
Power Output	NB: 10 W SATCOM: 20 W WB: 20 W peak/5 W average
Antenna Outputs	NB: 30 MHz-512 MHz SATCOM: 243 MHz-318 MHz WB: 225 MHz-2 GHz
Harmonic Suppression	Greater than 50 dBc

Receiver	
Narrowband Sensitivity (for 10 dB SINAD)	LOS FM 30-512 MHz: -118 dBm LOS AM 90-512 MHz: -110 dBm with 70% Modulation TACSAT FM 243-270 MHz: -120 dBm
Adjacent Channel Rejection	60 dB referenced to 10 dB SINAD (50 kHz channel) VHF: 60 dB (50 kHz off channel) UHF: 50 dB (50 kHz off channel)

Accessories Included with AN/PRC-117G	
10075-1399	H-250 Handset
RF-6650M	Communications Planning Application (CPA)
12043-0750-A006	USB Programming Cable
Manuals	Operation Manual, Reference Guide, SINCGARS Pocket Guide, ANW2 Pocket Guide

Optional Accessories	
RF-300M-DK001	Dismount Antenna Kit
RF-300M-VK001	Vehicular Antenna Kit
RF-300M-UK001	L-Band Rover Receiver Kit
RF-7800M-V150	50W Vehicular Amplifier Adapter
RF-7800M-V120	20W Vehicular Amplifier Adapter
RF-3071-AT232	GPS Antenna Kit (L1/L2 Band)
12043-2710-A006	PPP Data Cable
12043-2730-A006	Data and Remote Control Cable
12043-2740	Digital Retransmission Cable
12043-2760-A006	Ethernet Cable
RF-5910-PS005	Battery Eliminator
RF-7800B-DU024	BGAN Land Portable Antenna System
RF-7800B-VU104	BGAN Land Mobile Antenna System

"HAIPE" and the "HAIPE" design are trademarks of the National Security Agency, an agency of the United States Government and used with permission.



RF Communications | 1680 University Ave. | Rochester, NY USA 14610 | 585.244.5830 | www.harris.com

Get quotes real-time at eHarris. Order parts online at: <https://premier.harris.com/rfcommsales>

This information was approved for all publishing per the ITAR as "basic marketing in information of defense articles" or as "advertising printed matter" per the EAR. Specifications are subject to change without notice. Copyright © 2010 Harris Corporation 12/10 DS-357H